MHP15HD

TRAILER MOUNTED BOOM LIFTS



- Working height of up to 14.8m
- Heavy duty trailer mounted articulated boom lift
- Superb and efficient engine for a smooth and accurate response
- Easy to use outrigger/boom safety interlocks
- Ideal for a wide range of applications



TRAILER MOUNTED BOOM LIFTS


DIMENSIONS	MHP15HD
Max. working height	14.8m
Max. platform height (A)	12.8m
Horizontal outreach	7m at 8m
Platform size	1.24m x 0.77m 1.1m
Outrigger footprint	3.7m x 3.6m
Overall width (outriggers extended)	3.7m
Overall width (outriggers retracted) (B)	1.77m
Overall length (C)	7.45m
Transport height (D)	1.9m

PERFORMANCE	
Platform capacity	200kg
Max. wind speed	12.5m/s
Levelling	auto
Turntable rotation	540° non-continuous
Tyres	235/75 R15
Brakes	Hydraulic disc
Trailer tongue weight	90kg
Insulation rating	Nil


POWER	
Power source	Honda petrol engine 5.5hp
Hydraulic system	Proportional live/hydraulic

WEIGIII	
Gross weight	1,840kg

WORKING ENVELOPE



MHP15HD



STANDARD FEATURES

- Two person steel platform
- Tow coupling
- Jockey wheel
- Hydraulic disc brakes
- Reliable petrol engine
- Automatic stabilizers
- Hour meter
- Hydraullic outriggers
- Rotating basket mount

OPTIONS

- 10.9m height cut out switch
- Flashing light
- 110/240V RCD Protected power to platform
- Alternative power options
- Lifting lugs



Vigo Centre, Birtley Road, Washington, Tyne & Wear, NE38 9DA, U.K.

t: +44 (0) 845 1550 057 e: sales@snorkellifts.com